

# P/N NAS1802-3-11

### **Description**

Fastener Length: 23/32", Thread: 10-32, Thread Length: 23/32", NAS1802 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1802311

Minimum Qty (MOQ): 25

NSN: 5305-01-166-1693

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1802-3-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.610 Inches Minimum And 0.719 Inches Maximum
Fastener Length:	0.672 Inches Minimum And 0.719 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1802-3-11">https://military-fasteners.com/screws/machine+screws/NAS1802-3-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS1802-3-11">https://military-fasteners.com/screws/machine+screws/NAS1802-3-11</a> and selecting the quantity you