

Description

NAS1802-3-33 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1802333 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-332-6672 |
| Schedule B: | 7318.15.2000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1802-3-33 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.750 Inches Minimum And 2.093 Inches Maximum |
| Fastener Length: | 2.046 Inches Minimum And 2.093 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams5731 Assn Std Single Material Response Or Ams5732 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Bearing Surface Of Head Surface Finish: | 63.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1802 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.