

Description

Fastener Length: 2-21/64", Thread: 10-32, Thread Length: 1-3/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802337
Minimum Qty (MOQ):	5
NSN:	5305-01-361-6754
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1802-3-37 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	2.296 Inches Minimum And 2.343 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.