

P/N NAS1802-3-43

Military-Fasteners.com

## Description

Screw part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

## **Additional Information**

SKU / Model:	NAS1802343
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-338-7584
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1802-3-43 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	2.608 Inches Minimum And 2.685 Inches Maximum
Fastener Length:	2.672 Inches Minimum And 2.717 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1802-3-43</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.