

Description

length: 7/16", thread: 10-32, hex head, cruciform recess, full thread, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS180237 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-165-8608 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1802-3-7 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.358 Inches Minimum And 0.437 Inches Maximum |
| Fastener Length: | 0.422 Inches Minimum And 0.469 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Criticality Code Justification: | Feat |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ms 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Special Features: | Weapons System Essential |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1802 Professional/Industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.