

**Description**

Fastener Length: 15/32", Thread: 10-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS180237P
Minimum Qty (MOQ):	35 EA
NSN:	5305-01-603-8563
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N NAS1802-3-7P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.358 Inches Minimum And 0.437 Inches Maximum
<b>Fastener Length:</b>	0.422 Inches Minimum And 0.469 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.105 Inches Minimum And 0.120 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.314 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Screw Hex Head Cruciform Recess Full Thread A286 Cres
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Surface Treatment:</b>	Cadmium
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-7P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.