

Description

length: 1/2", thread: 10-32, hex head screw, cruciform recess, full thread, corrosion resistant steel, cad plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS180238P
Minimum Qty (MOQ):	10
NSN:	5305-01-585-3098
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1802-3-8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.450 Inches Minimum And 0.499 Inches Maximum
Fastener Length:	0.484 Inches Minimum And 0.531 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw Hex Head Cruciform Recess Full Thread A286 Cres 160 Ksi FtU
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.