

P/N NAS1802-3-9P

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 37/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS180239P

Minimum Qty (MOQ): 25

NSN: 5305-01-587-9174

Schedule B: 7318.15.6080

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1802-3-9P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.505 Inches Minimum And 0.585 Inches Maximum
Fastener Length:	0.569 Inches Minimum And 0.616 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams5731 Or Ams5732 Or Ams 5737 Or Ams5853 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1802-3-9P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.