

Description

Fastener Length: 1-9/64", Thread: 10-32, Thread Length: 63/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18023D16
Minimum Qty (MOQ):	5
NSN:	5305-01-472-0576
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N NAS1802-3D16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.9200 Inches Minimum And 0.9990 Inches Maximum
Fastener Length:	1.0890 Inches Minimum And 1.1510 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response
Special Features:	Has Drilled Head
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3D16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.