

Description

Fastener Length: 2-11/64", Thread: 10-32, Thread Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS18023D34 |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5305-01-471-8875 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS1802-3D34 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.9450 Inches Minimum And 2.0240 Inches Maximum |
| Fastener Length: | 2.1140 Inches Minimum And 2.1760 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response |
| Special Features: | Has Drilled Head |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3D34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.