

## P/N NAS1802-3D5

## **Description**

Fastener Length: 11/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS18023D5

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-523-9859

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1802-3D5 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.2965 Inches Minimum And 0.3435 Inches Maximum
Fastener Length:	0.2965 Inches Minimum And 0.3435 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
End Item Identification:	F-15 Acft
Nominal Thread Diameter:	0.1900 Inches
Hole Quantity:	3
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Criticality Code Justification:	Aasb
Part Name Assigned By Controlling Agency:	Screw,hex Head
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5732 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Or Ams5853 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Hexagon Corners
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1802-3D5">https://military-fasteners.com/screws/machine+screws/NAS1802-3D5</a> and selecting the quantity you want

