

Description

Fastener Length: 1-37/64", Thread: 1/4-28, Thread Length: 1-33/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802425
Minimum Qty (MOQ):	10
NSN:	5305-01-548-8644
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1802-4-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.498 Inches Minimum And 1.530 Inches Maximum
Fastener Length:	1.546 Inches Minimum And 1.592 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
End Item Identification:	Aircraft Osprey V-22a
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw,hex Head, Cruciform Recess
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	A286 Cres (uns S66286) Conforming To The Chemistry Of Ams5731, Ams5732, Ams5737 Or Ams5853 Mfr Ref Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205 - Nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.