

Description

Fastener Length: 1-5/8", Thread: 1/4-28, Thread Length: 1-5/8", hex head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802426
Minimum Qty (MOQ):	5
NSN:	5305-01-444-7382
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1802-4-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.625 Inches Nominal
Fastener Length:	1.625 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.