

**Description**

Fastener Length: 1/4", Thread: 1/4-28, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS180244
Minimum Qty (MOQ):	1
NSN:	5305-01-592-3236
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1802-4-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.250 Inches Nominal
<b>Fastener Length:</b>	0.250 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.410 Inches Minimum
<b>Internal Drive Style:</b>	Cross Recess Type Iii
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Or Ams5732 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Or Ams5853 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Ams 2700, Method 1, Type 2 Or 8, Class 1 Assn Std Single Treatment Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.