

Description

Fastener Length: 1-1/16", Thread: 1/4-32, Thread Length: 63/64", drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18024D16
Minimum Qty (MOQ):	10
NSN:	5305-01-587-9186
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1802-4D16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.960 Inches Minimum And 1.039 Inches Maximum
Fastener Length:	1.024 Inches Minimum And 1.071 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	A286 (uns S66286) Conforming To Chemistry Of Ams5731 Or Ams5732 Or Ams5737 Or Ams5853 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Ams2700, Method 1, Type 2 Or Type 8, Class 1 Assn Std Single Treatment Response
Special Features:	Has Drilled Head With 3 Holes Drilled Across Adjacent Sides; Holes Are 0.046 To 0.056 Inch In Diameter
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4D16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.