

Description

Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18024D17
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-561-0415
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1802-4D17 Specifications

Thread Direction:	Right-hand
Thread Length:	0.880 Inches Nominal
Head Style:	Hexagon
Head Height:	0.073 Inches Nominal
Width Between Flats:	0.372 Inches Nominal
Hole Diameter:	0.051 Inches Nominal
Internal Drive Style:	Cross Recess Type li
End Item Identification:	Np2000 Propeller Control; E2 Hawkeye Aircraft
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	3
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Hex Head Screw
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ms5731 Assn Std Single Material Response And 5732 Assn Std Single Material Response And Ms5731 Assn Std Single Material Response
Bearing Surface Of Head Surface Treatment:	Cadmium
Head Surface Treatment:	Cadmium
Screw Surface Treatment:	Cadmium
Shank Surface Treatment:	Cadmium
Special Features:	Used To Hold Brush Block Assembly In Place
Color:	Silver
Supplementary Features:	T.o. (fr)01-e2aaa-4-3
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.