

Description

Fastener Length: 7/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS18024D7 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-433-4776 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1802-4D7 Specifications

| | |
|---|--|
| Thread Class: | Jf |
| Thread Direction: | Right-hand |
| Thread Length: | 0.4375 Inches Nominal |
| Fastener Length: | 0.4375 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 3 |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Hexagon Flats |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1802 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4D7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.