

Description

Fastener Length: 5-29/32", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 1-3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18024D94
Minimum Qty (MOQ):	1
NSN:	5305-01-531-3636
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1802-4D94 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	5.859 Inches Minimum And 5.906 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	3
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Hexagon Corners
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1802 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-4D94> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.