

Description

NAS1804-12 Self-Locking Extended Washer Nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS180412
Minimum Qty (MOQ):	2
NSN:	5310-01-109-6057
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1804-12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	1.181 Inches Minimum And 1.221 Inches Maximum
Counterbore Diameter:	0.750 Inches Minimum Nut And 0.785 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.750 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.094 Inches Nominal
Width Across Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.750 Inches
Material:	Steel Comp H11 Overall Or Steel Comp 601 Overall
Material Document And Classification:	Ams 6487 Assn Std 1st Material Response Overall Or Ams 6403 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec All Treatment Responses Overall
Specification/standard Data:	80205-nas1804 Professional/Industrial Association Standard

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1804-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.