

Description



Thread: 10-32, 12 point self-locking nut, extended washer, cadmium plated alloy steel, dry film lube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18043
Minimum Qty (MOQ):	10
NSN:	5310-01-186-9306
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1804-3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.299 Inches Minimum
Lubrication:	Dry Film Lubricant
Overall Height:	0.190 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.015 Inches Nominal
Width Across Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 601 Overall Or Steel Comp H11 Overall
Material Document And Classification:	Ams 6304 Assn Std 1st Material Response Overall Or Ams 6487 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1804 Professional/industrial Association Standard

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1804-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.