

**Description**

thread: 3/8-24, 12 point, self locking, extended, cadmium plated alloy steel, dry film lube, NAS1804 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS18046
Minimum Qty (MOQ):	10
NSN:	5310-01-187-6109
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1804-6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.631 Inches Maximum
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Height:</b>	0.375 Inches Maximum
<b>Nut Style:</b>	Double Hexagon
<b>Washer Thickness:</b>	0.056 Inches Nominal
<b>Width Across Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	24
<b>Hardness Rating:</b>	45.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Material:</b>	Steel Comp 601 Overall Or Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6304 Assn Std 1st Material Response Overall Or Ams 6487 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1804 Professional/Industrial Association Standard

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/NAS1804-6](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1804-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.