

Description

thread: 1/2-20, 12 point, self locking, extended washer, cadmium plated alloy steel, dry film lube, NAS1804 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS18048 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-109-6058 |
| Schedule B: | 7318.16.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1804-8 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.828 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.500 Inches Maximum |
| Nut Style: | Double Hexagon |
| Washer Thickness: | 0.074 Inches Nominal |
| Width Across Flats: | 0.616 Inches Minimum And 0.627 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Hardness Rating: | 45.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.500 Inches |
| Material: | Steel Comp 601 Overall Or Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6304 Assn Std 1st Material Response Overall Or Ams 6487 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,class 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1804 Professional/industrial Association Standard |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1804-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.