

P/N NAS1804-9

Description

thread: 9/16-18, 12 point. self locking, extended washer, cadmium plated alloy steel, dry film lube, NAS1804 series nut

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS18049

Minimum Qty (MOQ):

NSN: 5310-01-109-6059

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1804-9 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.926 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.562 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.079 Inches Nominal
Width Across Flats:	0.679 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Hardness Rating:	45.0 Rockwell C Maximum
Nominal Thread Size:	0.562 Inches
Material:	Steel Comp 601 Overall Or Steel Comp H11 Overall
Material Document And Classification:	Ams 6304 Assn Std 1st Material Response Overall Or Ams 6487 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1804 Professional/industrial Association Standard

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self-locking+extended+washer+nuts/NAS1804-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self-locking+extended+washer+nuts/NAS1804-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self-locking+extended+washer+nuts/NAS1804-9.