

Description

Thread: 5/16-24, 12 point, self locking, extended washer, corrosion resistant steel, NAS1805 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS18055 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-197-2573 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1805-5 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.532 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.312 Inches Maximum |
| Nut Style: | Double Hexagon |
| Washer Thickness: | 0.035 Inches Nominal |
| Width Across Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1805 Professional/industrial Association Standard |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1805-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.