

## **P/N NAS1805-5L**

### **Description**

thread: 5/16-24, 12 point, self-locking, extended washer, cadmium plated corrosion resistant steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS18055L

Minimum Qty (MOQ): 10

NSN: 5310-01-314-3078

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1805-5L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.532 Inches Maximum
Overall Height:	0.312 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.035 Inches Nominal
Width Across Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall Or Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec 1st Treatment Response Overall Or Qq-p-416,ty 2,cl 2 Fed Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1805 Professional/industrial Association Standard

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1805-5L">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1805-5L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.