

P/N NAS1829C3C06

Military-Fasteners.com

Description

Thread Size: 7/64", Head Width: 3/16", Thread Length: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1829C3C06
Minimum Qty (MOQ):	10
NSN:	5340-01-223-7949
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N NAS1829C3C06 Specifications

Thread Class:	2a Right External
Thread Class:	2b Left Internal (includes Thru Thread)
Thread Direction:	Right-hand Left Internal (includes Thru Thread)
Thread Direction:	Right-hand Right External
Thread Length:	0.250 Inches Nominal Left Internal (includes Thru Thread)
Thread Length:	0.184 Inches Minimum Right External And 0.192 Inches Maximum Right External
Length:	0.3700 Inches Minimum And 0.3800 Inches Maximum
Cross-sectional Shape:	Hexagon
Width Across Flats:	0.1820 Inches Minimum And 0.1940 Inches Maximum
Thread Quantity Per Inch:	40 Left Internal (includes Thru Thread)
Thread Quantity Per Inch:	40 Right External
Nominal Thread Size:	0.1120 Inches Right External
Nominal Thread Size:	0.1120 Inches Left Internal (includes Thru Thread)
Right Projection Diameter:	0.1120 Inches Nominal
Right Projection Length:	0.1840 Inches Minimum And 0.1920 Inches Maximum
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Astm-a-582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Left Internal And Right External Thread
Thread Series Designator:	Unc Left Internal (includes Thru Thread)
Thread Series Designator:	Unc Right External

How to Order

Order this electrical post from our inventory online by visiting <u>https://military-fasteners.com/electrical/electrical/electrical+posts/NAS1829C3C06</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.