

Description

Thread Size: 5/32", Head Width: 5/16", Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1831A5D56
Minimum Qty (MOQ):	10
NSN:	5340-01-459-4252
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N NAS1831A5D56 Specifications

Thread Class:	2b Left Internal (includes Thru Thread)
Thread Class:	2b Right Internal
Thread Direction:	Right-hand Left Internal (includes Thru Thread)
Thread Direction:	Right-hand Right Internal
Thread Length:	0.4380 Inches Nominal Left Internal (includes Thru Thread)
Thread Length:	0.4380 Inches Nominal Right Internal
Length:	3.4950 Inches Minimum And 3.5050 Inches Maximum
Cross-sectional Shape:	Hexagon
Width Across Flats:	0.3070 Inches Minimum And 0.3190 Inches Maximum
Thread Quantity Per Inch:	32 Left Internal (includes Thru Thread)
Thread Quantity Per Inch:	32 Right Internal
Nominal Thread Size:	0.1640 Inches Left Internal (includes Thru Thread)
Nominal Thread Size:	0.1640 Inches Right Internal
Material:	Aluminum Alloy 6061 Standoff Or Aluminum Alloy 2024 Standoff Or Aluminum Alloy 2011 Standoff
Material Document And Classification:	Qq-a-225/8 Fed Spec Single Material Response Standoff Or Qq-a-225/6 Fed Spec Single Material Response Standoff Or Qq-a-225/3 Fed Spec Single Material Response Standoff
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty 1 Or Ty 2, Cl 1 Mil Spec Single Treatment Response Standoff
Style Designator:	Left Internal And Right Internal Threads
Thread Series Designator:	Unc Left Internal (includes Thru Thread)
Thread Series Designator:	Unc Right Internal

How to Order

Order this electrical post from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+posts/NAS1831A5D56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.