

Description

length: 3/8", thread: 6-32, blind threaded sandwich panel, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1832063
Minimum Qty (MOQ):	10
NSN:	5325-01-240-9085
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N NAS1832-06-3 Specifications

Flange Diameter:	0.550 Inches Minimum And 0.560 Inches Maximum
Flange Thickness:	0.060 Inches Nominal
Length:	0.375 Inches Nominal
Second Flange Thickness:	0.030 Inches Minimum
Width Across Flats:	0.400 Inches Nominal
Insert Size:	0.300 In. Od
Features Provided:	Individually Keyed
Material:	Steel Overall
Material Document And Classification:	Fed Std 66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flange
Specification/standard Data:	80205-nas1832 Professional/Industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832-06-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.