

**Description**

length: 3/8", thread: 6-32, blind threaded sandwich panel, cadmium plated carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1832063
Minimum Qty (MOQ):	10
NSN:	5325-01-240-9085
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N NAS1832-06-3 Specifications

<b>Flange Diameter:</b>	0.550 Inches Minimum And 0.560 Inches Maximum
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Length:</b>	0.375 Inches Nominal
<b>Second Flange Thickness:</b>	0.030 Inches Minimum
<b>Width Across Flats:</b>	0.400 Inches Nominal
<b>Insert Size:</b>	0.300 In. Od
<b>Features Provided:</b>	Individually Keyed
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Fed Std 66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flange
<b>Specification/standard Data:</b>	80205-nas1832 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832-06-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.