

**Description**

length: 3/8", thread: 8-32, blind threaded sandwich panel, cadmium plated carbon steel, NAS1832 series insert

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1832083M
Minimum Qty (MOQ):	10
NSN:	5325-01-165-7775
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1832-08-3M Specifications

<b>Flange Diameter:</b>	0.550 Inches Minimum And 0.560 Inches Maximum
<b>Overall Length:</b>	0.375 Inches Nominal
<b>Hole Type:</b>	Threaded
<b>Features Provided:</b>	Potting Hole Or Potting Slot
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Insert Style:</b>	Protruding Flange
<b>Special Features:</b>	Solid Film Lubricant On Inside Of Insert Only
<b>Material:</b>	Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1012 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1025 Overall Or Steel Comp 1030 Overall Or Steel Comp 1035 Overall Or Steel Comp 1040 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Size And Series/type Designator:</b>	0.164-32 Unjc
<b>Specification/standard Data:</b>	80205-nas1832 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832-08-3M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.