

Description

Insert part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS183235M |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5325-01-080-6679 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1832-3-5M Specifications

| | |
|---|--|
| Flange Diameter: | 0.550 Inches Minimum And 0.560 Inches Maximum |
| Overall Length: | 0.625 Inches Nominal |
| Hole Type: | Threaded |
| Features Provided: | Potting Hole Or Potting Slot |
| Flange Thickness: | 0.060 Inches Nominal |
| Insert Style: | Protruding Flange |
| Special Features: | Solid Film Lubricant On Inside Of Insert Only |
| Material: | Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1012 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1025 Overall Or Steel Comp 1030 Overall Or Steel Comp 1035 Overall Or Steel Comp 1040 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Size And Series/type Designator: | 0.190-32 Unjf |
| Specification/standard Data: | 80205-nas1832 Professional/industrial Association Standard |

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832-3-5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.