

**Description**

Screw Thread Insert part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1832C33M
Minimum Qty (MOQ):	10
NSN:	5325-01-165-7776
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1832C3-3M Specifications

<b>Flange Diameter:</b>	0.550 Inches Minimum And 0.560 Inches Maximum
<b>Overall Length:</b>	0.375 Inches Nominal
<b>Hole Type:</b>	Threaded
<b>Features Provided:</b>	Potting Hole Or Potting Slot
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Insert Style:</b>	Protruding Flange
<b>Special Features:</b>	Solid Film Lubricant On Inside Of Insert Only
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall Or Silver Overall Or Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Overall Or Ams 2410 Assn Std 2nd Treatment Response Overall Or Qq-p-416,ty 2,cl 2 Fed Spec 3rd Treatment Response Overall
<b>Thread Size And Series/type Designator:</b>	0.190-32 Unjf
<b>Specification/standard Data:</b>	80205-nas1832 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832C3-3M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.