

Description

Length: 5/8", thread: 10-32, insert, blind threaded sandwich panel, corrosion resistant steel, NAS1832 series insert

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1832C35
Minimum Qty (MOQ):	10
NSN:	5325-01-165-8989
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1832C3-5 Specifications

Thread Class:	3b
Flange Thickness:	0.060 Inches Nominal
Length:	0.625 Inches Nominal
Second Flange Thickness:	0.030 Inches Minimum
Insert Size:	0.300 In. Dia
Features Provided:	Individually Keyed
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Small Flange With Wrenching Flats 0.400 In. W Across Flats
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Flange
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1832 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832C3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.