

Description

Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1832C35M |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-01-165-8989 |
| Schedule B: | 7318.16.0060 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1832C3-5M Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Flange Thickness: | 0.060 Inches Nominal |
| Length: | 0.625 Inches Nominal |
| Second Flange Thickness: | 0.030 Inches Minimum |
| Insert Size: | 0.300 In. Dia |
| Features Provided: | Individually Keyed |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Special Features: | Small Flange With Wrenching Flats 0.400 In. W Across Flats |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flange |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1832 Professional/Industrial Association Standard |

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832C3-5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.