

Description

Insert part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1832C38M
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-299-1993
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1832C3-8M Specifications

Flange Diameter:	0.550 Inches Minimum And 0.560 Inches Maximum
Overall Length:	0.370 Inches Minimum
Hole Type:	Threaded
Features Provided:	Potting Hole And Potting Slot
Flange Thickness:	0.060 Inches Nominal
Insert Style:	Protruding Flange
Special Features:	Solid Film Lubricant Per Mil-I-8937; Apply On Inside Of Insert Only
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Precious Material And Location:	Overall Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall Or Cadmium Overall And Chromate Overall Or Passivate Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std 1st Treatment Response Overall Or Qq-p-416,type 2,class 2 Fed Spec 2nd Treatment Response Overall Or Qq-p-35 Fed Spec 3rd Treatment Response Overall
Thread Size And Series/type Designator:	0.190-32 Unjf
Specification/standard Data:	80205-nas1832 Professional/industrial Association Standard

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1832C3-8M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.