

**Description**

length: 0.250", thread: 10-32, insert, thru threaded sandwich panel, cadmium plated carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS18333250
Minimum Qty (MOQ):	25
NSN:	5325-01-167-9698
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N NAS1833-3-250 Specifications

<b>Thread Class:</b>	3b
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Length:</b>	0.250 Inches Nominal
<b>Second Flange Thickness:</b>	0.060 Inches Nominal
<b>Insert Size:</b>	0.300 In. Min,0.375 In. Max Dia
<b>Features Provided:</b>	Individually Keyed
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flange
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1833 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1833-3-250> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.