

Description

NAS1833A3-375

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1833A3375 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-174-4831 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |



* See page 2 for technical characteristics

P/N NAS1833A3-375 Specifications

| | |
|--|--|
| Flange Diameter: | 0.550 Inches Minimum And 0.560 Inches Maximum |
| Overall Length: | 0.375 Inches Nominal |
| Hole Type: | Threaded |
| Features Provided: | Potting Hole And Potting Slot |
| Flange Thickness: | 0.060 Inches Nominal |
| Insert Style: | Protruding Flange |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-225/6,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 1 Mil Spec Single Treatment Response Overall |
| Thread Size And Series/type Designator: | 0.190-32 Unjf |
| Specification/standard Data: | 80205-nas1833 Professional/industrial Association Standard |

How to Order

Order this panel fastener insert from our inventory online by visiting <https://military-fasteners.com/inserts/panel+fastener+inserts/NAS1833A3-375> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.