

Description

NAS1833C3

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	NAS1833C3750
Minimum Qty (MOQ):	10
NSN:	5325-01-357-4725
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1833C3-750 Specifications

Flange Diameter:	0.550 Inches Minimum And 0.560 Inches Maximum
Overall Length:	0.750 Inches Nominal
Material Accommodated Thickness:	0.561 Inches Minimum And 0.566 Inches Maximum
Hole Type:	Threaded
Features Provided:	Potting Hole And Potting Slot
Flange Thickness:	0.060 Inches Nominal
Insert Style:	Protruding Flange
Special Features:	Solid Film Lubricant Apply On Threads Only
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Size And Series/type Designator:	0.190-32 Unjf
Specification/standard Data:	80205-nas1833 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1833C3-750> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.