

P/N NAS1833C3-750

Description

NAS1833C3

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1833C3750

Minimum Qty (MOQ): 10

NSN: 5325-01-357-4725

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS1833C3-750 Specifications

| Flange Diameter: | 0.550 Inches Minimum And 0.560 Inches Maximum |
|--|--|
| Overall Length: | 0.750 Inches Nominal |
| Material Accommodated Thickness: | 0.561 Inches Minimum And 0.566 Inches Maximum |
| Hole Type: | Threaded |
| Features Provided: | Potting Hole And Potting Slot |
| Flange Thickness: | 0.060 Inches Nominal |
| Insert Style: | Protruding Flange |
| Special Features: | Solid Film Lubricant Apply On Threads Only |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Size And Series/type Designator: | 0.190-32 Unjf |
| Specification/standard Data: | 80205-nas1833 Professional/industrial Association Standard |

How to Order

Order this screw thread insert from our inventory online by visiting https://military-fasteners.com/inserts/screw+thread+inserts/NAS1833C3-750 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/inserts/screw+thread+inserts/NAS1833C3-750 and selecting the