

P/N NAS1834-3K500

Description

length: 0.50" clearance hole: 0.195" - 0.201", countersunk thru clearance hole, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS18343K500

Minimum Qty (MOQ): 25

NSN: 5325-01-367-9346

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









^{*} See page 2 for technical characteristics

P/N NAS1834-3K500 Specifications

Shoulder Diameter:	0.196 Inches Nominal
Flange Diameter:	0.550 Inches Minimum And 0.560 Inches Maximum
Talige Diameter.	0.550 litelies Millimulti Alia 0.500 litelies Maximulti
Overall Length:	0.500 Inches Nominal
Material Accommodated Thickness:	0.561 Inches Minimum And 0.566 Inches Maximum
Hole Type:	Plain
Features Provided:	Potting Hole Or Potting Slot
Insert Style:	Protruding Flange
Hole Diameter:	0.196 Inches Nominal
Special Features:	Countersunk Clearance Hole
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1834 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting https://military-fasteners.com/inserts/screw+thread+inserts/NAS1834-3K500 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/inserts/screw+thread+inserts/NAS1834-3K500 and selecting the