

P/N NAS1835A08

Description

NAS1835 series insert

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1835A08

Minimum Qty (MOQ): 10

NSN: 5325-01-043-6064

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









^{*} See page 2 for technical characteristics

P/N NAS1835A08 Specifications

Shoulder Diameter:	0.535 Inches Nominal
Flange Diameter:	0.675 Inches Minimum And 0.685 Inches Maximum
Overall Length:	0.370 Inches Nominal
Hole Type:	Threaded
Features Provided:	Potting Hole Or Potting Slot
Body Diameter:	0.164 Inches Nominal
Insert Style:	Protruding Flange
Material:	Aluminum Alloy 2024 Housing
Material:	Aluminum Alloy Cap
Material:	Steel Comp 1006 Nut Or Steel Comp 1008 Nut Or Steel Comp 1010 Nut Or Steel Comp 1012 Nut Or Steel Comp 1015 Nut Or Steel Comp 1016 Nut Or Steel Comp 1017 Nut Or Steel Comp 1018 Nut Or Steel Comp 1019 Nut Or Steel Comp 1020 Nut Or Steel Comp 1021 Nut Or Steel Comp 1022 Nut Or Steel Comp 1025 Nut Or Steel Comp 1030 Nut Or Steel Comp 1035 Nut Or Steel Comp 1040 Nut
Material Document And Classification:	66 Fed Std All Material Responses Nut
Material Document And Classification:	Qq-a-225/6,t4 Fed Spec Single Material Response Housing
Surface Treatment:	Anodize Cap Or Chromate Cap
Surface Treatment:	Anodize Housing
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment Document And Classification:	Mil-a-8625,ty 1 Mil Spec 1st Treatment Response Cap Or Mil-c-5541,cl 3 Mil Spec 2nd Treatment Response Cap
Surface Treatment Document And Classification:	Mil-a-8625,ty 1 Mil Spec Single Treatment Response Housing
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
Thread Size And Series/type Designator:	0.164-32 Unjc
Specification/standard Data:	80205-nas1835 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting https://military-fasteners.com/inserts/screw+thread+inserts/NAS1835A08 and selecting the

