

## P/N NAS1836-06-13

## **Description**

length: 0.406", thread: 6-32, insert, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

| SKU / Model:       | NAS18360613      |
|--------------------|------------------|
| Minimum Qty (MOQ): | 10               |
| NSN:               | 5325-01-421-4172 |
| ECCN:              | EAR99            |



# P/N NAS1836-06-13 Specifications

| Thread Class:                                  | 3b   |
|--|--|
| Thread Length:                                 | 0.187 Inches Nominal   |
| Flange Diameter:                               | 0.450 Inches Nominal   |
| Flange Thickness:                              | 0.060 Inches Nominal   |
| Length:  | 0.403 Inches Nominal   |
| Features Provided:                             | Self-locking   |
| Thread Quantity Per Inch:                      | 32   |
| Nominal Thread Size:                           | 0.138 Inches   |
| Material:                                      | Steel Comp 1008 Overall  |
| Material Document And Classification:          | Astm A 108 Assn Std Single Material Response Overall               |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall                               |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Style Designator:                              | Flange   |
| Thread Series Designator:                      | Unjc   |

## **How to Order**

Order this screw thread insert from our inventory online by visiting <a href="https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-06-13">https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-06-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-06-13">https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-06-13</a> and selecting the