

Description

Length: 0.219", thread: 8-32, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS18360807 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5325-01-579-4244 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS1836-08-07 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Thread Length: | 0.187 Inches Nominal |
| Flange Diameter: | 0.450 Inches Nominal |
| Flange Thickness: | 0.060 Inches Nominal |
| Length: | 0.217 Inches Nominal |
| Second Flange Thickness: | 0.060 Inches Nominal |
| Width Across Flats: | 0.260 Inches Nominal |
| Insert Size: | 0.250 |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Part Name Assigned By Controlling Agency: | Insert, Molded In, Blind Threaded, Self-locking, Lightweight, Sandwich Panel |
| Material: | Steel Overall |
| Material Document And Classification: | Astm A108 Assn Std Single Material Response Overall Or Astm A576 Assn Std Single Material Response Overall Or 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ams Qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall |
| Style Designator: | Flange |
| Thread Series Designator: | Unjc |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-08-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.