

Description

length: 0.25", thread: 8-32, insert, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18360808
Minimum Qty (MOQ):	10
NSN:	5325-01-358-5615
ECCN:	EAR99
National Motor Freight:	094560, Fasteners Box / Pail / Tub Noi Steel



P/N NAS1836-08-08 Specifications

Flange Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Material Accommodated Thickness:	0.452 Inches Minimum And 0.457 Inches Maximum
Sleeve Diameter:	0.260 Inches Nominal
Hole Type:	Threaded
Features Provided:	Potting Slot
Flange Thickness:	0.060 Inches Nominal
Insert Style:	Protruding Flange
Special Features:	0.248 In. Lg
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Size And Series/type Designator:	0.164-32 Unjc
Specification/standard Data:	80205-nas1836 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-08-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.