

Description

Length: 0.343", thread: 8-32, insert, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS18360811 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5325-01-166-2699 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS1836-08-11 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Flange Diameter: | 0.441 Inches Minimum And 0.451 Inches Maximum |
| Flange Thickness: | 0.060 Inches Nominal |
| Length: | 0.341 Inches Nominal |
| Second Flange Thickness: | 0.060 Inches Nominal |
| Width Across Flats: | 0.260 Inches Nominal |
| Insert Size: | 0.250 In. Nom Dia |
| Features Provided: | Individually Keyed |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flange |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas1836 Professional/industrial Association Standard |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-08-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.