

**Description**

length: 0.250", thread: 10-32, insert, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1836308
Minimum Qty (MOQ):	25
NSN:	5325-01-357-8691
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N NAS1836-3-08 Specifications

<b>Flange Diameter:</b>	0.441 Inches Minimum And 0.451 Inches Maximum
<b>Sleeve Diameter:</b>	0.260 Inches Nominal
<b>Hole Type:</b>	Threaded
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Insert Style:</b>	Protruding Flange
<b>Special Features:</b>	Pin Overall Length Is 0.250 Inch Nominal
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec All Treatment Responses Overall
<b>Thread Size And Series/type Designator:</b>	0.190-32 Unjf

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-3-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.