

## P/N NAS1836-3-12M

### **Description**

Insert part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1836312M

Minimum Qty (MOQ): 15 EA

NSN: 5325-01-371-3146

National Motor Freight: 095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1836-3-12M Specifications

Flange Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Sleeve Diameter:	0.260 Inches Nominal
Hole Type:	Threaded
Features Provided:	Potting Slot Or Potting Hole
Flange Thickness:	0.060 Inches Nominal
Insert Style:	Protruding Flange
Special Features:	With Dry Film Lubricant
Material:	Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1012 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1025 Overall Or Steel Comp 1035 Overall Or Steel Comp 1040 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl2 Fed Spec Single Treatment Response Overall
Thread Size And Series/type Designator:	0.190-32 Unjf
Specification/standard Data:	80205-nas1836 Professional/industrial Association Standard

## **How to Order**

Order this insert from our inventory online by visiting <a href="https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-3-12M">https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-3-12M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.