

Description

length: 0.62", thread: 10-32, blind threaded sandwich panel, lightweight, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1836320
Minimum Qty (MOQ):	25
NSN:	5325-01-166-2701
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1836-3-20 Specifications

Thread Class:	3b
Flange Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Flange Thickness:	0.060 Inches Nominal
Length:	0.620 Inches Nominal
Second Flange Thickness:	0.060 Inches Nominal
Width Across Flats:	0.260 Inches Nominal
Insert Size:	0.250 In. Nom Dia
Features Provided:	Individually Keyed
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flange
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1836 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836-3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.