

**Description**

length: 0.219", thread: 8-32, insert, blind threaded sandwich panel, lightweight - corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1836C0807
Minimum Qty (MOQ):	10
NSN:	5325-01-324-4503
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N NAS1836C08-07 Specifications

<b>Flange Diameter:</b>	0.441 Inches Minimum And 0.451 Inches Maximum
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Length:</b>	0.218 Inches Nominal
<b>Insert Size:</b>	Aa0.260
<b>Features Provided:</b>	Individually Keyed
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flange
<b>Specification/standard Data:</b>	80205-nas1836 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C08-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.