

Description

Insert part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1836C0809M |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5325-01-158-9956 |
| Schedule B: | 7318.16.0060 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1836C08-09M Specifications

| | |
|---|--|
| Flange Diameter: | 0.441 Inches Minimum And 0.451 Inches Maximum |
| Flange Thickness: | 0.060 Inches Nominal |
| Length: | 0.281 Inches Nominal |
| Insert Size: | 0.260 In. Dia |
| Full Internal Thread Length: | 0.187 Inches Nominal |
| Features Provided: | Individually Keyed |
| Special Features: | Solid Film Lubricant,mil-I-8937 Inside Of Insert Only |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1836 Professional/industrial Association Standard |

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C08-09M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.